ASMPT enabling the digital world



SIPLACE X S

Maximum capacity for an intelligent factory

MAXIMUM PLACEMENT PERFORMANCE SIPLACE X S

THE NEW STANDARD IN HIGH-VOLUME PRODUCTION

Tailor-made for your production, the new SIPLACE X S is the machine of choice for demanding high-volume applications. Robust placement heads and intelligent feeders ensure an extremely fast placement process while smart sensors and a unique digital vision system provide maximum precision and process reliability. Innovations like fast and precise PCB warpage detection complete the overall package.

The SIPLACE X S is the perfect solution for telecommunication/5G, IT/ server and other demanding applications where you want to be a step ahead of the competition with non-stop processes, maximum yields, extreme productivity, and the lowest placement costs.

THE HEAD MAKES THE DIFFERENCE

THREE INNOVATIVE PLACEMENT HEADS DELIVER PERFORMANCE, FLEXIBILITY AND BALANCE.



Modular, flexible, open – Standard interfaces and a growing number of automation options make the SIPLACE X S the number one choice for your demanding high-volume production applications in the intelligent factory.







Placement Head CP20

- Component spectrum: 0201 metric to 8.2 mm x 8.2 mm x 4 mm
- Extremely fast with up to 43,000 cph

Placement Head CPP

- Switches from pick-and-place to collectand-place to mixed mode
- Component height: Up to 15.5 mm
- Component weight: Up to 20 g

Placement Head TWIN

- Component height: Up to 25 mm
- Component weight: Up to 160 g
- Snap-in detection

OUR GOAL: **REDUCING PLACEMENT COSTS**



Maximum performance

Innovative placement modes raise the placement performance to up to 172,000 cph



Maximum placement quality

The unique digital vision system, sensor technology and smart feeders ensure maximum placement quality



Total flexibility

Intelligent placement head technologies ensure perfectly balanced lines with any product mix



Smart solution

Intelligent, self-healing systems and state-of-the-art software reduce manual assists to an absolute minimum



Predictive maintenance

Sensors and software capture the machine's behavior for predictive and preventive maintenance



SMART **WORKFLOWS**

WORKS SOFTWARE SUITE

With the WORKS Software Suite, you get the most out of your SIPLACE X S high-volume production line and lay the foundation for your intelligent factory. It makes your employees' work easier in their respective areas, controls and optimizes the production flow, and calculates the component requirements during the assembly process. AMR fleet management applications and enterprise solutions such as MES and ERP software can be easily connected.

Open and standard-based interfaces such as IPC-HERMES-9852 and IPC-CFX ensure consistent M2M and M2H communication.

More about the SIPLACE X S



SIPLACE X S

Technical data*	SIPLACE X2 S	SIPLACE X3 S	SIPLACE X4 S
Speed (benchmark rating**)	75,000 cph	112,500 cph	150,000 cph
Speed (IPC rating)	65,000 cph	97,050 cph	130,000 cph
Feeder slots	160 x 8 mm		
Component spectrum	0201 metric to 200 mm × 110 mm × 25 mm		
Board sizes	50 mm × 50 mm to 850 mm × 685 mm		
Machine dimensions (L x W x H)	1.9 m × 2.6 m × 1.6 m		
Placement heads	Placement Head CP20, Placement Head CPP, Placement Head TWIN		
Placement accuracy	22 μm @ 3 σ (with Placement Head TWIN)		
Conveyors	Single conveyor, flexible dual conveyor		

^{*} Professional maintenance in accordance with the intervals and scope recommended by ASMPT ensures that your SIPLACE equipment complies with specified performance and accuracy values across its entire life cycle. We offer custom-tailored maintenance contracts. Please contact us.

ASMPT

ASMPT GmbH & Co. KG

Rupert-Mayer-Strasse 48 | 81379 Munich | Germany | Phone: +49 89 20800-22000 | Email: smt-solutions.de@asmpt.com

⊕ asmpt.com | ⊕ smt.asmpt.com

All information and illustrations in this brochure are provided "as is" and without any warranties of any kind, whether expressed or implied, including but not limited to, implied warranties of satisfactory quality, fitness for a particular purpose and/or correctness.

The contents of this brochure are for general information purposes only, do not constitute advice, and are subject to change without notice. ASMPT therefore makes no warranties or representations regarding the use of the content, details, specifications or information contained in this brochure in terms of their correctness, accuracy, adequacy, usefulness, timeliness, reliability or otherwise, in each case to the fullest extent permitted by law. Please contact ASMPT for the most current information. Any specific performance features and/or capabilities will only be binding if contractually agreed upon.

All product names are brands or trademarks of ASMPT or other suppliers. Unauthorised use by third parties may violate the rights of their owners.

^{**} SIPLACE benchmark